

WHAT IS CLAIMED IS:

1. An information recording apparatus comprising:
a light source which emits a recording light for
5 information recording;
a recording waveform data generating unit which generates
recording waveform data which is predetermined digital data
corresponding to an input recording signal;
a D/A converting unit which D/A-converts the recording
10 waveform data to generate a driving pulse signal; and
a driving unit which drives the light source to emit
the recording light based on the driving pulse signal, wherein
the recording waveform data is determined in accordance with
characteristics of the light source, the driving unit and a
15 combination thereof.

2. The information recording apparatus according to
claim 1, wherein the recording waveform data generating unit
comprises:
20 a unit which generates a recording strategy signal based
on the recording signal and strategy information;
a storing unit which stores predetermined waveform data
determined in accordance with the characteristics of the light
source, the driving unit and the combination thereof, for pulse
25 waveforms of plural pulse widths; and
a generating unit which obtains the waveform data
corresponding to the pulse waveform forming the strategy signal
from the storing unit and generates the recording waveform data.

30 3. The information recording apparatus according to
claim 1, wherein the recording waveform data generating unit
comprises:
a storing unit which stores predetermined waveform data
determined in accordance with the characteristics of the light

source, the driving unit and the combination thereof, for recording waveform corresponding to plural recording signals; and

5 a generating unit which obtains waveform data corresponding to the input recording signal from the storing unit and generates the recording waveform data.

10 4. The information recording apparatus according to claim 2, wherein the storing unit stores the waveform data for each of a recording power which is a power of a recording light emitted from the light source in recording, and the generating unit refers to the storing unit according to a recording power to be utilized and generates the recording waveform data.

15 5. The information recording apparatus according to claim 1, wherein the recording waveform data includes a level for suppressing an overshoot and/or an undershoot at a position corresponding to a position at which a waveform of the recording light emitted from the light source forms the overshoot and/or
20 the undershoot.

6. The information recording apparatus according to claim 1, wherein the recording waveform data has a level for canceling a level tilt in a case that a waveform of a recording
25 light emitted from the light source has the level tilt.

7. An information recording method executed by an information recording apparatus which comprises a light source which emits a recording light for information recording and a
30 driving unit of the light source, comprising:

a process which generates recording waveform data which is predetermined digital data corresponds to an input recording signal and determined in accordance with characteristics of the light source, the driving unit and a combination thereof;

a process which generates a driving pulse signal by D/A-converting the recording waveform data; and

a process which performs information recording by driving the light source by the driving unit to emit the recording light
5 based on the driving pulse signal.

8. An information recording apparatus comprising:

a light source which emits a recording light for information recording;

10 a strategy signal generating unit which generates a strategy signal which is a pulse waveform signal corresponding to the input recording signal;

a correcting data generating unit which generates correcting data which is predetermined digital data
15 corresponding to an input recording signal;

a D/A converting unit which D/A-converts the correcting data to generate correcting signal which is an analog signal;

an adding unit which adds the strategy signal and the correcting signal to generate a driving pulse signal; and

20 a driving unit which drives the light source to emit the recording light based on the driving pulse signal, wherein the correcting data is determined in accordance with characteristics of the light source, the driving unit and a combination thereof.

25

9. The information recording apparatus according to claim 8, wherein the correcting data includes a level for suppressing an overshoot and/or an undershoot at a position corresponding to a position at which a waveform of a recording
30 light emitted from the light source forms the overshoot and/or the undershoot.

10. The information recording apparatus according to claim 8, wherein the correcting data has a level for canceling

a level tilt in a case that a waveform of a recording light emitted from the light source includes the level tilt.

11. An information recording method which is executed
5 by an information recording apparatus including a light source which emits a recording light for information recording and a driving unit of the light source, comprising:

a process which generates a strategy signal which is a pulse waveform signal corresponding to an input recording
10 signal;

a process which generates correcting data which corresponds to the input recording signal and is digital data predetermined in accordance with characteristics of the light source, the driving unit and a combination thereof;

15 a process which D/A-converts the correcting data to generate a correcting signal which is an analog signal;

a process which adds the strategy signal and the correcting signal to generate a driving pulse signal; and

20 a process which executes information recording by driving the light source to emit the recording light based on the driving pulse signal.

12. A waveform data generating device comprising:

25 a unit which obtains set waveform data which is digital data corresponding to a recording signal;

a D/A converting unit which D/A-converts the set waveform data to generate a driving pulse signal;

a driving unit which drives a light source by the driving pulse signal to emit a recording light;

30 a light detecting unit which receives the recording light and generates a detecting signal;

an A/D converting unit which A/D-converts the detecting signal and generates detected waveform data;

a unit which compares a prepared target waveform data

and the detected waveform data to calculate error data;
a unit which updates the set waveform data in a case that the error data is larger than a predetermined allowable error; and
5 a unit which stores corresponding set waveform data as waveform data corresponding to the recording signal in a case that the error data is smaller than the predetermined allowable error.

10 13. A waveform data generating method comprising:
a first process which obtains set waveform data which is digital data corresponding to a recording signal;
a second process which D/A-converts the set waveform data to generate a driving pulse signal;
15 a third process which drives a light source by the driving pulse signal to emit a recording light;
a fourth process which receives the recording light and generates a detecting signal;
a fifth process which A/D-converts the detecting signal
20 and generates detected waveform data;
a sixth process which compares a prepared target waveform data and the detected waveform data and calculates error data;
and
a process which updates the set waveform data and repeats
25 the processes from the first process to the sixth process in a case that the error data is larger than a predetermined allowable error; and
a process which stores corresponding set waveform data as waveform data corresponding to the recording signal in a case
30 that the error data is smaller than the predetermined allowable error.